# Mobile Air Heater GD



Photo shows fully equipped GD65.

The GD mobile air heaters are designed for cost effective spot heating in a wide variety of applications, including greenhouses, poultry houses and other livestock structures

## **Technology basis**

The GD heaters function on the principle of direct fired oil heating. Hereby a powerful fan is used to force air through a combustion chamber where the burner is situated. As the air passes through the burner, all the heat released by the combustion process is transferred to the air stream. This gives the heater a 100% thermal efficiency. The GD heaters operate on oil, kerosene or paraffin.

### Design

To ensure a long life span, the combustion chamber is manufactured in stainless steel, while the remainder of the heater is painted with unleaded epoxydic powder paint.


For safety purposes the heaters are equipped with a photoelectric flame detection sensor, flame control box and automatic electric control device.

All models are equipped with a fuel tank, wheels and electrical cord. The GD heaters come fully assembled (wheels and handle bar are disassembled for ease of transportation), ready for use. Optionally the heaters can be supplied with a mechanical or electronic thermostat. The thermostats have a 10m cable attached in order to be able to measure the temperature where it is required.

### **EQUIPMENT**


## **GD**

- 100% thermal efficiency
- · Ideal for spot heating
- Easy to install
- · Easy to operate
- Functions on diesel, kerosene or paraffin
- Photoelectric flame detection safety device
- Safety switch preventing overheating
- Stainless steel combustion chamber
- Built-in oil filter









## **Dimensions** [mm]

Heater size	A	В	С	D	Е
GD65	1,393	624	798	308	578
GD115	1,694	700	978	443	680

## **Technical specifications**

		GD65	GD115
Weight	[kg]	65	101
Heating power	[kW]	66	115.3
	[kCal/h]	56,700	99,100
Oil consumption	[l/h]	6.07	10.6
Tank capacity	[1]	51	100
Nominal electrical power	[W]	460	800
Voltage	[V]	230	230
Airflow	$[m^3/h]$	2,800	4,800
	[cfm]	1,660	2,850

GD is a product of Munters Italy S.p.A., Italy.



## **Order information**

GD-XXX-X-X e.g., GD115-b-1

Code for specifying size and type

115

Code for specifying thermostat

- a No thermostat
- b Mechanical thermostat
- c Digital thermostat

Code for specifying chimney kit -

- 1 With chimney kit
- 2 Without chimney kit



Munters, HumiCool Division, Isafjordsgatan 1, P.O. Box 1150, SE-164 26 Kista, Sweden. Phone +46 8 626 63 00, Fax +46 8 754 56 66.

Munters Italy S.p.A., Corso Inghilterra 15, 12084 Mondovì, Italy. Phone +39 0174 560 600, Fax +39 0174 560 617.

www.munters.com

Australia Munters Pty Limited, Phone +61 2 6025 6422, Brazil Munters Brasil Industria e Comercio Ltda, Phone +55 41 3317 5050, Canada Munters Incorporated, Phone +1 905 858 5894, China Munters Air Treatment Equipment (Beijing) Co. Ltd., Phone +86 10 80 481 121, Denmark Munters Turbovent, Phone +45 862 3311, Finland Munters O, Phone +358 983 86 030, France Munters France S.A., Phone +33 1 34 11 57 50, Germany Munters Euroform GmbH, Phone +49 241 89 00 0, India Munters India, Phone +91 20 3052 2520, Indonesia Munters, Phone +62 21 9105 4467, Italy Munters Italy S.p.A., Chiusavecchia Phone +39 0183-52 11, Munters Italy S.p.A., Mondovi Phone +39 0174 560 600, Japan Munters K.K., Phone +81 3 5970 0021, Kingdom of Saudi Arabia and Middle East Hawa Munters, Phone +966 1 241 8808, Korea Munters Korea Co. Ltd., Phone +82 2 761 8701, Mexico Munters Mexico, Phone +52 818 262 54 00, Russia Munters Europe AB, Phone +7 812 448 5740, Singapore Munters Pte Ltd., Phone +65 744 6828, South Africa and Sub-Sahara Countries Munters (Pty) Ltd., Phone +27 11 997 2000, Spain Munters Spain S.A., Phone +34 91 640 09 02, Sweden Munters Curporation Fort Myers Phone +1 239 936 1555, Munters Corporation Mason Phone +1 888 335 0100, Vietnam Munters Vietnam, Phone +84 8 825 6838, Export & Other Countries Munters Europe AB, Phone +46 8 626 63 00.

Your closest distributor